
EVEREX SYSTEMS, INC. EV8120, EV-8120A



Copyright © 1991, 1992, 1993, 1994 by Micro House Int'l (800) 926-8299. Research Dept. (303) 443-389.

EVEREX SYSTEMS, INC. EV8120, EV-8120A

. . . continued from previous page

CONNECTIONS	
Function	Location
34-pin control cable connector-floppy drive	J1
40-pin control cable connector-hard drive	J2
34-pin control cable connector-floppy tape drive (EV-8120A only)	J3
4-pin connector drive active LED	J9

USER CONFIGURABLE SETTINGS EV-8120 & EV-8120A					
Function	Location	Setting			
í IOCHRDY signal disabled	JP1	open			
IOCHRDY signal enabled	JP1	closed			
í DMA request disabled	JP2/all	open			
DREQ 5 (DMA request)	JP2/jumper 1	closed			
DREQ 6 (DMA request)	JP2/jumper 2	closed			
DREQ 7 (DMA request)	JP2/jumper 3	closed			
DMA acknowledge disabled	JP3/all	open			
DACK 5 (DMA acknowledge)	JP3/jumper 1	closed			
DACK 6 (DMA acknowledge)	JP3/jumper 2	closed			
DACK 7 (DMA acknowledge)	JP3/jumper 3	closed			
DMA signal to the ATA adaptor disabled	JP4	open			
DMA signal to the ATA adaptor enabled	JP4	closed			
í BIOS is IBM, AMI or equivalent	JP6	pins 2 & 3 closed			
BIOS is Phoenix	JP6	pins 1 & 2 closed			
í Factory configured - do not alter	JP7	open			
í Floppy drive enabled	JP8	closed			
Floppy drive disabled	JP8	open			
í Back to back I/O delay enabled	JP10	closed			
Back to back I/O delay disabled	JP10	open			

Continued on next page . . .

EVEREX SYSTEMS, INC. EV8120, EV-8120A

. . . continued from previous page

П	USER CONFIGURABLE SETTINGS EV-8120 ONLY				
	Function	Location	Setting		
ĺ	Hard drive port address is 1F0-1F7h	JP5	open		
	Floppy drive port address is 3F0-3F7h				
ĺ	Hard drive port address is 310-317h	JP5	closed		
	Floppy drive port address is 318-31Fh				

		-			
USER CONFIGURABLE SETTINGS EV-8120A ONLY					
Function	Location	Setting			
í ATA Hard Disk mode select	JP5	open			
ATA Tape Mode select	JP5	closed			
í Floppy drive port address is 3F0-3F7h	JP11	open			
Floppy drive port address is 370-377h	JP11	closed			
Hard drive port address is 1F0-1F7h	JP12	open			
Hard drive port address is 170-177h	JP12	closed			
Hard drive interrrupt is IRQ14	JP13	pins 2 & 3 closed			
Hard drive interrrupt is IRQ15	JP13	pins 1 & 2 closed			

Copyright © 1991, 1992, 1993, 1994 by Micro House Int'l (800) 926-8299. BBS (303) 443-9957.