



FUTURE DOMAIN CORPORATION TMC-1660, TMC-1680 (SURFACE MOUNT VERSIONS)

Q4/92

Data bus:	16-bit, ISA
Size:	TMC-1660: Half-length, full-height card TMC-1680: Full-length, full-height card
Hard drives supported:	Up to six SCSI devices
Floppy drives supported:	TMC-1660: None TMC-1680: Four 360KB, 720KB, 1.2MB, or 1.44MB
Sector interleave:	1:1



The TMC-1660



The TMC-1680

Continued on next page . . .

FUTURE DOMAIN CORPORATION TMC-1660, TMC-1680 (SURFACE MOUNT VERSIONS)

... continued from previous page

CONNECTIONS	
Function	Location
DB-25 SCSI connector-external	J1
50-pin SCSI connector-internal	J2
4-pin connector-drive active LED	J3
34-pin control cable connector-floppy drive	J5
34-pin control cable connector-floppy drive	J6

USER CONFIGURABLE SETTINGS		
Function	Location	Setting
í Termination Power enabled	F1	closed
Termination Power disabled	F1	open
í Primary floppy drive enabled (TMC-1680 only)	W2/jumper 1*	closed
Second floppy drive enabled (TMC-1680 only)	W2/jumper 2*	closed
í Hard drive enabled (TMC-1680 only)	W2/jumper 3	closed
Hard drive disabled (TMC-1680 only)	W2/jumper 3	open
í Termination ground	W3/jumpers 1-4	closed
Note: *These jumpers are mutually exclusive.		

INTERRUPT REQUEST			
IRQ	W1/jumper 1	W1/jumper 2	W1/jumper 3
IRQ3	open	open	open
IRQ5	closed	open	open
IRQ10	open	closed	open
IRQ11	closed	closed	open
IRQ12	open	open	closed
IRQ14	closed	open	closed
IRQ15	open	closed	closed
Disabled	closed	closed	closed

Continued on next page ...

FUTURE DOMAIN CORPORATION TMC-1660, TMC-1680 (SURFACE MOUNT VERSIONS)

. . . continued from previous page

I/O PORT ADDRESS		
Address	W1/jumper 4	W1/jumper 5
0140-014Fh	open	open
0150-015Fh	closed	open
0160-016Fh	open	closed
0170-017Fh	closed	closed

BIOS ADDRESS		
Address	W1/jumper 6	W1/jumper 7
CA000-CBFFFh	closed	open
C8000-C9FFFh	open	open
CE000-CFFFFh	open	closed
DE000-DFFFFh	closed	closed