
Q4/92

TRANTOR SYSTEMS, LTD. T100

Data bus: 8-bit, ISA

Size: Half-length, full-height card
Hard drives supported: Up to seven SCSI devices

Floppy drives supported: None



CONNECTIONS	
Function	Location
50-pin SCSI connector-internal	CN1
50-pin SCSI connector-external	CN2

	USER CONFIGURABLE SETTINGS		
	Function Location Setting		
ĺ	SCSI parity check enabled	SW1/switch 3	off
	SCSI parity check disabled	SW1/switch 3	on
ĺ	BIOS enabled	SW1/switch 6	off
	BIOS disabled	SW1/switch 6	on

Continued on next page . . .

Copyright © 1991, 1992, 1993 by Micro House Int'l (800) 926-8299. Research Dept. (303) 443-389.

TRANTOR SYSTEMS, LTD. T100

. . . continued from previous page

	I/O PORT ADDRESS	
Address	SW1/switch 1	SW1/switch 2
320h	off	off
324h	off	on
328h	on	off
32Ch	on	on

	BIOS ADDRESS	
Address	SW1/switch 4	SW1/switch 5
C8000h	off	off
CA000h	on	off
CC000h	off	on
CE000h	on	on

	DMA CHANNEL	
DRQ	JP1	Position
DRQ1	pins 7 & 9 and 8 & 10 only	closed
DRQ3	pins 9 & 11 and 10 & 12 only	closed
Disabled	pins 7 through 12	open

	INTERRUPT REQUEST	
IRQ	JP1	Position
IRQ3	pins 2 & 4 only	closed
IRQ5	pins 1 & 3 only	closed
IRQ6	pins 4 & 5 only	closed
IRQ7	pins 3 & 5 only	closed
Disabled	pins 1 through 6	open

MISCELLANEOUS TECHNICAL NOTES
This controller contains no on-board software.