


UNIDENTIFIED  
MAGIC I/O PM-540G

Q4/92

Data bus: 16-bit, ISA  
Size: Half-length, full-height card  
Hard drives supported: Two IDE (AT) Interface drives  
Floppy drives supported: Two 360KB, 720KB, 1.2MB, or 1.44MB



CONNECTIONS		
Function	Location	
4-pin connector-drive active LED	J1	
40-pin IDE Interface (AT) connector	J2	
34-pin control cable connector-floppy drive	J3	
9-pin serial port 2 (COM2)-internal	J4	
9-pin serial port 1 (COM1)-external	J5	
25-pin parallel port-external	J6	
15-pin game port-internal	J7	

USER CONFIGURABLE SETTINGS		
Function	Location	Setting
Floppy drive enabled	JP1 and JP2	closed
Floppy drive disabled	JP1 and JP2	open

Continued on next page . . .

# UNIDENTIFIED MAGIC I/O PM-540G

... continued from previous page

PARALLEL PORT (CN6) CONFIGURATION		
LPT	JP3/pins 1 & 2	JP3/pins 3 & 4
í LPT1 (378-37Fh)	open	closed
LPT2 (278-27Fh)	closed	open
Disabled	open	open

SERIAL PORT 2 (CN4) CONFIGURATION		
COM	JP3/pins 5 & 6	JP3/pins 7 & 8
í COM2 (2F8-2FFh)	open	closed
COM4 (2E8-2EFh)	closed	open
COM3 (3E8-3EFh)	closed	closed
Disabled	open	open

SERIAL PORT 1 (CN5) CONFIGURATION		
COM	JP3/pins 9 & 10	JP3/pins 11 & 12
í COM1 (3F8-3FFh)	open	closed
COM3 (3E8-3EFh)	closed	open
COM4 (2E8-2EFh)	closed	closed
Disabled	open	open

SERIAL PORT 1 (CN5) INTERRUPT REQUEST			
IRQ	JP4/pins 1 & 2	JP4/pins 3 & 4	JP4/pins 5 & 6
í IRQ4	closed	open	open
IRQ5	open	closed	open
IRQ9	open	open	closed

SERIAL PORT 2 (CN4) INTERRUPT REQUEST			
IRQ	JP4/pins 7 & 8	JP4/pins 9 & 10	JP4/pins 11 & 12
í IRQ3	closed	open	open
IRQ9	open	closed	open
IRQ5	open	open	closed

PARALLEL PORT (CN6) INTERRUPT REQUEST		
IRQ	JP4/pins 13 & 14	JP4/pins 15 & 16
í IRQ7	open	closed
IRQ5	closed	open
Disabled	open	open