


DISTRIBUTED PROCESSING TECHNOLOGY
PM2021A/90, PM2021A/95

Q4/93

Data bus: 16-bit, ISA (PM2021A/9x)
Size: Half-length, full-height card
Hard drive supported: Up to seven SCSI drives
Floppy drives supported: Two 360KB, 720KB, 1.2MB, or 1.44MB drives (PM2x2x/95 only)



CONNECTIONS	
Function	Location
CM4000 Cache Module Connector	P1
CM4000 Cache Module Connector	P2
DM4000 Disk Array Module Connector	P5
4-pin connector-Drive active LED	P6
DM400 Disk Array Module Connector	P7
34-pin control cable connector-floppy drive	P8
50-pin SCSI connector - internal	P10
50-pin SCSI connector - external	J11

Continued on next page . . .

DISTRIBUTED PROCESSING TECHNOLOGY

PM2021A/90, PM2021A/95

... continued from previous page

DMA TRANSFER RATE			
Speed	Jumper Y12	Jumper Y13	Jumper Y14
10MB/sec	open	open	open
8MB/sec	closed	open	open
6.667MB/sec	open	closed	open
5.7MB/sec	closed	closed	open
5.0MB/sec	open	open	closed
4.4MB/sec	closed	open	closed
4.0MB/sec	open	closed	closed
3.0MB/sec	closed	closed	closed

SCSI ADDRESS			
SCSI I.D.	Jumper Y18	Jumper Y25	Jumper Y26
0	open	open	open
1	open	closed	open
2	closed	open	open
3	closed	closed	open
4	open	open	closed
5	open	closed	closed
6	closed	open	closed
7	closed	closed	closed

INTERRUPT REQUEST		
IRQ	Y29	Y30
Disabled	open	open
IRQ12	open	closed
IRQ15	closed	open
IRQ14	closed	closed

DMA CHANNEL		
DRQ	Y31	Y32
DRQ0	open	open
DRQ7	open	closed
DRQ6	closed	open
DRQ5	closed	closed

Continued on next page ...

DISTRIBUTED PROCESSING TECHNOLOGY

PM2021A/90, PM2021A/95

Q4/93

... continued from previous page

I/O PORT ADDRESS		
Address	Y33	Y35
230h	open	open
f 170h	open	closed
330h	closed	open
1F0h	closed	closed

BIOS ADDRESS		
Address	Y36	Y37
Disabled	open	open
DC00h	open	closed
D800h	closed	open
f C800h	closed	closed

USER CONFIGURABLE SETTINGS		
Function	Location	Setting
f DMA duty cycle is fast	Y15	open
DMA duty cycle is slow	Y15	closed
f SCSI termination enabled	Y16	closed
SCSI termination disabled	Y16	open
f Address LInes SA17-19 and LA17-19 driven	Y19	closed
Only Address LInes LA17-19 driven	Y19	open
f Floppy drive enabled	Y20	closed
Floppy drive disabled	Y20	open
f Bus Mastering enabled	Y24	closed
Bus Mastering disabled	Y24	open
f BIOS ROM size is 8K	Y38	open
BIOS ROM size is 16K	Y38	closed
f External SCSI cable detection disabled	Y39	open
External SCSI cable detection enabled*	Y39	closed
f Controller supplies TERMPWR to SCSI interface	Y50	closed
26 TERMPWR not supplied to SCSI Interface 26	Y50	open

Continued on next page ...

DISTRIBUTED PROCESSING TECHNOLOGY

PM2021A/90, PM2021A/95

. . . continued from previous page

STATUS LED'S	
LED	Definition
LED 1	Busy
LED 2	Computer Bus Transfer to Adapter
LED 3	Computer Bus Transfer from Adapter
LED 4	Cache Hit
LED 5	Disk Read-Ahead Active
LED 6	Disk Read
LED 7	Disk Write
LED 8	Adapter Reset
LED 9	Interrupt Pending to Computer
LED 10	DRQ Asserted to Computer

MISCELLANEOUS TECHNICAL NOTES
<p>Detection of an external SCSI cable limits the maximum SCSI bus transfer rate to 5MB/sec. The function of Jumper Y34 is unknown.</p>