
Q1/94

PC WARE INTERNATIONAL, INC. V-U40821 I/O

Data bus: 16-bit, ISA

Half-length, full-height card Size: Two IDE (AT) Interface drives
Two 360KB, 720KB, 1.2MB, or 1.44MB drives Hard drive supported:

Floppy drives supported:



| CONNECTIONS | | | | |
|---|----------|--|--|--|
| Function | Location | | | |
| 40-pin IDE(AT) Interface connector | CN1 | | | |
| 34-pin control cable connector - floppy drive | CN2 | | | |
| 10-pin serial port (COM1/3) - internal | CN3 | | | |
| 10-pin serial port (COM2/4) - internal | CN4 | | | |
| 15-pin game port - internal | CN5 | | | |
| 26-pin VESA feature connector - internal | CN6 | | | |
| 15-pin VGA analog video port - external | CN7 | | | |
| 25-pin parallel port (LPT2/3) - external | CN8 | | | |
| 2-pin drive active LED | J2 | | | |

| USER CONFIGURABLE SETTINGS | | | |
|--|----------|-------------------|--|
| Function | Location | Setting | |
| í I/O Channel Ready signal disabled | J1 | open | |
| I/O Channel Ready signal enabled | J1 | closed | |
| í VGA port Interrupt Request IRQ2 disabled | J3 | open | |
| VGA port Interrupt Request IRQ2 enabled | J3 | closed | |
| í Serial Port 2 (CN4) is set to COM2 | JP1 | pins 1 & 2 closed | |
| Serial Port 2 (CN4) is set to COM4 | JP1 | pins 2 & 3 closed | |

Continued on next page . . .

PC WARE INTERNATIONAL, INC. V-U40821 I/O

. . . continued from previous page

| USER CONFIGURABLE SETTINGS | | | |
|---|----------|-------------------|--|
| Function | Location | Setting | |
| í Serial Port 1 (CN3) enabled | JP2 | pins 1 & 2 closed | |
| Serial Port 1 (CN3) disabled | JP2 | pins 2 & 3 closed | |
| í Serial Port 2 (CN4) enabled | JP3 | pins 1 & 2 closed | |
| Serial Port 2 (CN4) disabled | JP3 | pins 2 & 3 closed | |
| í Game Port (CN5) enabled | JP4 | pins 1 & 2 closed | |
| Game Port (CN5) disabled | JP4 | pins 2 & 3 closed | |
| í Parallel Port (CN8) is set to LPT2 | JP5 | pins 1 & 2 closed | |
| Parallel Port (CN8) is set to LPT3 | JP5 | pins 2 & 3 closed | |
| í Parallel Port (CN8) enabled | JP6 | pins 1 & 2 closed | |
| Parallel Port (CN8) disabled | JP6 | pins 2 & 3 closed | |
| Hard drive controller installation exists | JP7 | pins 1 & 2 closed | |
| Hard drive controller installation does not exist | JP7 | pins 2 & 3 closed | |
| í Serial Port 1 (CN3) is set to COM1 | JP8 | pins 1 & 2 closed | |
| Serial Port 1 (CN3) is set to COM3 | JP8 | pins 2 & 3 closed | |
| í Hard drive enabled | JP9 | pins 1 & 2 closed | |
| Hard drive disabled | JP9 | pins 2 & 3 closed | |
| í Floppy drive enabled | JP10 | pins 1 & 2 closed | |
| Floppy drive disabled | JP10 | pins 2 & 3 closed | |