
Q4/94

UNIDENTIFIED SAB-757

Data bus: 16-bit, ISA

Size: Half-length, full-height card Hard drive supported: Two IDE (AT) interface drives

Floppy drives supported: Two 360KB, 720KB, 1.2MB, or 1.44MB drives



CONNECTIONS		
Function	Location	
25-pin parallel port	CN1	
9-pin serial port 1 - external	CN2	
10-pin serial port 2 - internal	CN3	
Game port	CN4	
34-pin control cable connector - floppy drive	CN5	
40-pin IDE (AT) Interface connector	CN6	
2-pin connector - drive active LED	JP5	

USER CONFIGURABLE SETTINGS		
Function	Location	Setting
í IDE port enabled	JP1/jumper A	Pins 2 & 3 closed
IDE port disabled	JP1/jumper A	Pins 1 & 2 closed
í Floppy drive enabled	JP1/jumper B	Pins 2 & 3 closed
Floppy drive disabled	JP1/jumper B	Pins 1 & 2 closed

SERIAL PORT 1 CONFIGURATION		
COM/Address	JP1/Jumper C	JP1/Jumper D
í C)M1/3F8h	Pins: & 3 closed	Pins & 2 closed
C)M3/3E8h	Pins & 2 closed	Pins: & 3 closed
C)M4/2E8h	Pins: & 3 closed	Pins: & 3 closed
)isabled	Pins & 2 closed	Pins & 2 closed

Continued on next page . . .

UNIDENTIFIED SAB-757

. . . continued from previous page

SERIAL PORT 2 CONFIGURATION		
COM/Address	JP1/Jumper E	JP1/Jumper F
í C)M2/2F8h	Pins: & 3 closed	Pins & 2 closed
C)M3/3E8h	Pins: & 3 closed	Pins: & 3 closed
C)M4/2E8h	Pins & 2 closed	Pins: & 3 closed
)isabled	Pins & 2 closed	Pins & 2 closed

PARALLEL PORT CONFIGURATION		
LPT/Address	JP1/Jumper G	JP1/Jumper H
í L 'T1/3BCh	Pins: & 3 closed	Pins: & 3 closed
l ٬T2/378h	Pins & 2 closed	Pins: & 3 closed
l ٬T3/278h	Pins: & 3 closed	Pins & 2 closed
Disabled	Pins & 2 closed	Pins & 2 closed

PARALLEL PORT INTERRUPT SELECT		
IRQ	JP1	
í IRQ7	Pins 2 & 3 clo ed	
IRQ5	Pins 1 & 2 clo ed	