

ATLANTIC COMPUTER PRODUCTS, INC.

GP4530

... continued from previous page

I/O PORTS CONFIGURATION							
Floppy	Serial 1	Serial 2	Parallel	JP1	JP2	JP4	JP5
Enabled	COM1	COM2	LPT1	1 & 2	1 & 2	2 & 3	1 & 2
Enabled	COM1	COM2	LPT2	2 & 3	1 & 2	2 & 3	1 & 2
Enabled	COM3	COM4	LPT2	1 & 2	2 & 3	2 & 3	1 & 2
Enabled	COM2	COM3	LPT1	2 & 3	2 & 3	2 & 3	1 & 2
Disabled	COM1	COM2	LPT1	1 & 2	1 & 2	1 & 2	2 & 3
Disabled	COM1	COM2	LPT2	2 & 3	1 & 2	1 & 2	2 & 3
Disabled	COM3	COM4	LPT2	1 & 2	2 & 3	1 & 2	2 & 3
Disabled	COM2	COM3	LPT1	2 & 3	2 & 3	1 & 2	2 & 3
Enabled	Disabled	Disabled	Disabled	1 & 2	2 & 3	2 & 3	2 & 3
Disabled	Disabled	Disabled	Disabled	2 & 3	2 & 3	2 & 3	2 & 3
Note: The pins indicated are in the closed position.							

WAIT STATE		
Setting	JP8	JP9
Wait State 2 enabled	pins 2 & 3 closed	pins 2 & 3 closed
Wait State 1 enabled	pins 2 & 3 closed	pins 1 & 2 closed
Wait State 3 enabled	pins 1 & 2 closed	pins 2 & 3 closed
Wait State 4 enabled	pins 1 & 2 closed	pins 1 & 2 closed

VIDEO MEMORY CONFIGURATION				
Memory Size	JP10	JP11	Bank 0	Bank 1
1MB	pins 2 & 3 closed	pins 1 & 2 closed	(2) 512K x 8	None
2MB	pins 2 & 3 closed	pins 2 & 3 closed	(2) 512K x 8	(2) 512K x 8