


BUSLOGIC, INC.
BT-410CD

Q4/95

Data bus: 32-bit VESA local bus
Size: Three quarter-length, full-height card
Hard drive supported: Four IDE (AT) interface drives, Two ATAPI devices
Floppy drives supported: Two 360KB, 720KB, 1.2MB, 1.44MB drives



CONNECTIONS	
Function	Location
40-pin connector - IDE (AT) interface 1	CN1
40-pin connector - IDE (AT) interface 2	CN2
34-pin connector - Floppy drive interface	CN3
40-pin connector - ATAPI interface	CN4
4-pin connector - Drive active LED	JP1
4-pin connector - Speaker	JP2

USER CONFIGURABLE SETTINGS		
Function	Location	Setting
ATAPI mode enabled	JP3	closed
ATAPI mode disabled	JP3	open
Note: If you are using two BT-410CD units in the same system, both cards must have ATAPI mode disabled.		

Continued on next page. . .

BUSLOGIC, INC.
BT-410CD

...continued from previous page

DRAM CONFIGURATION		
Size	Bank 0	Bank 1
512KB	(2) 256K x 9	NONE
1MB	(2) 256K x 9	(2) 256K x 9
2MB	(2) 1M x 9	NONE
2.5MB	(2) 1M x 9	(2) 256K x 9
2.5MB	(2) 256K x 9	(2) 1M x 9
4MB	(2) 1M x 9	(2) 1M x 9
8MB	(2) 4M x 9	NONE
8.5MB	(2) 4M x 9	(2) 256K x 9
8.5MB	(2) 256K x 9	(2) 4M x 9
10MB	(2) 4M x 9	(2) 1M x 9
10MB	(2) 1M x 9	(2) 4M x 9
16MB	(2) 4M x 9	(2) 4M x 9