## ABIT COMPUTER CORPORATION MI300

Size: Hard drive supported:	32-bit, VL-bus Half-length, half-height card Two IDE (AT) Interface drives Two 360KB, 720KB, 1.2MB, or 1.44MB dri	Q2/95
	JP4-JP12 HOUSE	
	CONNECTIONS Function	Location
40-pin IDE(AT) Interface co		CN1
34-pin control cable connector - floppy drive		CN2
Game port	1.1.2	CN3
9-pin serial port 1 - external		CN4
10-pin serial port 2 - interna		CN5
25-pin parallel port		CN6
2-pin connector - drive activ		JP1

USER CONFIGURABLE SETTINGS			
Function	Location	Setting	
í IDE port enabled	JP4	pins 1 & 2 closed	
IDE port disabled	JP4	pins 2 & 3 closed	
í Floppy drive enabled	JP7	pins 1 & 2 closed	
Floppy drive disabled	JP7	pins 2 & 3 closed	
í Game Port enabled	JP11	pins 1 & 2 closed	
Game Port disabled	JP11	pins 2 & 3 closed	

Continued on next page . . .

Copyright © 1991, 1992, 1993 by Micro House Int'l (800) 926-8299. Research Dept. (303) 443-3389

## ABIT COMPUTER CORPORATION MI300

... continued from previous page

	HARD DRIVE SPEED	
Setting	JP2	JP3
í Speed 2	pins 1 & 2 closed	pins 2 & 3 closed
Speed 0	pins 1 & 2 closed	pins 1 & 2 closed
Speed 1	pins 2 & 3 closed	pins 2 & 3 closed
Speed 3	pins 2 & 3 closed	pins 1 & 2 closed

PARALLEL PORT CONFIGURATION		
LPT/Address	JP5	JP10
í LPT2/378h	pins 1 & 2 closed	pins 1 & 2 closed
LPT3/278h	pins 1 & 2 closed	pins 2 & 3 closed
Disabled	pins 2 & 3 closed	n/a

SERIAL PORT 1 CONFIGURATION		
COM/Address	JP6	JP8
í COM1/3F8h	pins 1 & 2 closed	pins 1 & 2 closed
COM3/3E8h	pins 1 & 2 closed	pins 2 & 3 closed
Disabled	pins 2 & 3 closed	n/a

SERIAL PORT 2 CONFIGURATION		
COM/Address	JP9	JP12
í COM2/2F8h	pins 1 & 2 closed	pins 1 & 2 closed
COM4/2E8h	pins 1 & 2 closed	pins 2 & 3 closed
Disabled	pins 2 & 3 closed	n/a

Copyright  $\circledcirc$  1991, 1992, 1993 by Micro House Int'l (800) 926-8299. BBS (303) 443-9957