PROMISE TECHNOLOGY, INC.


DC5030E

Card TypeHard drive controllerHard Drives supportedFour IDE (AT) drives

Floppy drives supported None

Data Bus 32-bit PCI

Card Size Half-length, full-height



	CONNECTIONS			
•	Function	Location	Function	Location
	40-pin primary IDE(AT) connector	J1	Mini ISA IRQ support card connector	JP1
	40-pin secondary IDE(AT) connector	J2	4-pin connector - drive active LED	JP5

	JP1 CONNECTOR PIN-OUT		
Pin#	Function	Pin #	Function
1 - 3	Unidentified	5	IRQ15
4	IRQ14	6 - 14	Unidentified

USER CONFIGURABLE SETTINGS

Functio	n Label	Position
» ISA IRQ enabled	JP2	Closed
PCI IRQ enabled	JP2	Open
» Relocatable I/O address disabled	JP3	Pins 2 & 3 closed
Relocatable I/O address enabled	JP3	Pins 1 & 2 closed

ISA BIOS enabled	JP6	Pins 2 & 3 closed
PCI BIOS enabled	JP6	Pins 1 & 2 closed

BIOS ADDRESS SELECTION		
Address	JP3	
D8000h	Pins 4 & 5 closed	
DC000h	Pins 5 & 6 closed	
PCI INTER	RUPT SELECTION	
Setting	JP4	
INTA	Pins 1 & 3 closed	
NTD		
INTB	Pins 3 & 5 closed	
INTC	Pins 3 & 5 closed Pins 2 & 4 closed	

Note: The configuration of the cache memory is unidentified