


ADAPTEC, INC.
AHA-2842A

Card Type	Hard drive controller card
Hard Drives supported	Up to 7 SCSI devices
Floppy drives supported	Two 360KB, 720KB, 1.2MB, or 1.44MB drives
Data Bus	32-bit VESA Local Bus
Card Size	Full-length, full-height card



CONNECTIONS			
Function	Location	Function	Location
4-pin LED connector	J1	50-pin SCSI connector - internal	J3
34-pin Floppy drive connector	J2	50-pin SCSI connector - external	J4

USER CONFIGURABLE SETTINGS			
Function		Label	Position
Write-back enabled		J5	Closed
Write-back disabled		J5	Open
Floppy controller enabled		S1/5	Off
Floppy controller disabled		S1/5	On
Host adapter BIOS enabled		S1/8	Off
Host adapter BIOS disabled		S1/8	On

Continued on next page . . .

. . . continued from previous page

I/O ADDRESS SELECTION				
Address	S1/1	S1/2	S1/3	S1/4
í 1C00h	Off	Off	Off	Off
2C00h	On	Off	Off	Off
3C00h	Off	On	Off	Off
4C00h	On	On	Off	Off
5C00h	Off	Off	On	Off
6C00h	On	Off	On	Off
7C00h	Off	On	On	Off
8C00h	On	On	On	Off
9C00h	Off	Off	Off	On
AC00h	On	Off	Off	On
BC00h	Off	On	Off	On
CC00h	On	On	Off	On
DC00h	Off	Off	On	On
EC00h	On	Off	On	On
FC00h	Off	On	On	On
Reserved	On	On	On	On

BIOS ADDRESS SELECTION		
Address	S1/6	S1/7
C8000h	On	Off
D0000h	Off	On
í D8000h	Off	Off
E0000h	On	On