
EVEREX SYSTEMS, INC. EVERGRAPHICS PLUS EV-231C

CategoryVideoVideo Types SupportedMonochromeVideo Processor6845Highest Resolution720 x 348

Supported
Data Bus Type 8-bit ISA
Memory Type DRAM

Maximum Onboard Memory 64KB (Exact location of memory is unidentified)



CONNECTIONS				
Purpos :	Location	Purpos ;	Location	
Monochrome video port	PA5	Parallel port	PC5	

COLUMN (132) DISPLAY CONFIGURATION		
Setting	JD1A	
í Enabled	Pins 1 & 2 closed	
Disabled	Pins 2 & 3 closed	

PARALLEL PORT INTERRUPT SELECTION		
IRQ JE2		
í 7	Pins 2 & 3 closed	
5	Pins 1 & 2 closed	

Continued on next page . . .

EVEREX SYSTEMS, INC. EVERGRAPHICS PLUS EV-231C

. . . continued from previous page

PARALLEL PORT CONFIGURATION				
LP1	Addres	JA1		
í 1	3BCh - 3BEh	Pins 1 & 2 closed		
2	378h - 37Fh	Pins 3 & 4 closed		
3	278h - 27Fh	Pins 1 & 2, 3 & 4 closed		
Disabled	N/A	Open		

FACTORY CONFIGURED - DO NOT ALTER		
Jumper	Position	
JD1B	Closed	