
## EVEREX SYSTEMS, INC. EVERGRAPHICS PLUS EV-231D

CategoryVideoVideo Types SupportedMonochromeVideo Processor6845Highest Resolution720 x 348

Supported
Data Bus Type 8-bit ISA
Memory Type DRAM

Maximum Onboard Memory 64KB (Exact location of memory is unidentified)



CONNECTIONS			
Purpos :	Location	Purpos ;	Location
Monochrome video port	P2	Parallel port	P3

COLUMN (132) DISPLAY CONFIGURATION		
Setting	W1	
í Enabled	Pins 2 & 3 closed	
Disabled	Pins 1 & 2 closed	

PARALLEL PORT INTERRUPT SELECTION		
IRQ	IRQ	
ĺ7	Pins 2 & 3 closed	
5	Pins 1 & 2 closed	

Continued on next page . . .

## EVEREX SYSTEMS, INC. EVERGRAPHICS PLUS EV-231D

. . . continued from previous page

	PARALLEL PORT CONFIGURATION			
LPT	Ac Iress	V2	V3	
í1	3BCh - 3BEh	Pins 1 & 2 closed	Pins 2 & 3 closed	
2	378h - 37Fh	Pins 1 & 2 closed	Pins 1 & 2 closed	
3	278h - 27Fh	Pins 2 & 3 closed	Pins 1 & 2 closed	
Disabled	N/A	Pins 2 & 3 closed	Pins 2 & 3 closed	

FACTORY CONFIGURED - DO NOT ALTER		
Jumper	Position	
J1	Closed	