
## UNIDENTIFIED RY-3301

Category Video Types Supported Video Processor Highest Resolution Supported8-bit ISData Bus Type8-bit ISMemory TypeDRAMMaximum Onboard Memory64KB

Video CGA/Monochrome Unidentified 640 x 200

8-bit ISA DRAM



CONNECTIONS				
Purpos 🔅	Location	Purpo: >	Location	
Composite video connector	CN1	Parallel port	CN4	
Light pen connector	CN2	15-pin analog video port	CN5	
Bus mouse	CN3			

BUS MOUSE INTERRUPT SELECTION			
IRQ	CN6		
í 5	Pins 7 & 8 closed		
2/9	Pins 1 & 2 closed		
3	Pins 3 & 4 closed		
4	Pins 5 & 6 closed		

Continued on next page . . .

## UNIDENTIFIED RY-3301

. . . continued from previous page

MONITOR EMULATION CONFIGURATION					
lode	S V1/1	S V1/2	S V1/3		
í Color emulation	On	N/A	N/A		
Color	Off	On	On		
Auto switch via software	Off	N/A	Off		
Hercules	Off	Off	On		
Auto switch via software	Off	Off	Off		

PARALLEL PORT CONFIGURATION			
LPT	SW1/4		
í 1	Off		
2	On		