


GOLDSTAR ELECTRONICS INTERNATIONAL, INC.  
GW451C

Card Type	Multi I/O card
Chipset/Controller	Goldstar
I/O Options	Game port, parallel port, serial ports (2)
Maximum DRAM	N/A



CONNECTIONS			
Purpose :	Location	Purpose :	Location
Serial port 1	J1	Game port	P1
Serial port 2	J2	Parallel port	P2

SERIAL PORT CONFIGURATION				
Port 1 (J1)	JP1	JP2	JP3	JP4
COM1	Pins 1 & 2 closed	Pins 1 & 2 closed	N/A	Pins 1 & 2 closed
COM2	N/A	Pins 1 & 2 closed	Pins 2 & 3 closed	Pins 1 & 2 closed
COM3	Pins 2 & 3 closed	Pins 1 & 2 closed	N/A	Pins 1 & 2 closed
COM4	N/A	Pins 1 & 2 closed	Pins 1 & 2 closed	Pins 1 & 2 closed
Disabled	N/A	Pins 2 & 3 closed	N/A	Pins 2 & 3 closed

Continued on next page . . .

GOLDSTAR ELECTRONICS INTERNATIONAL, INC.  
GW451C

... continued from previous page

SERIAL PORT CONFIGURATION				
Port 2 (J2)	JP1	JP2	JP3	JP4
COM2	N/A	Pins 1 & 2 closed	Pins 2 & 3 closed	Pins 1 & 2 closed
COM1	Pins 1 & 2 closed	Pins 1 & 2 closed	N/A	Pins 1 & 2 closed
COM3	Pins 2 & 3 closed	Pins 1 & 2 closed	N/A	Pins 1 & 2 closed
COM4	N/A	Pins 1 & 2 closed	Pins 1 & 2 closed	Pins 1 & 2 closed
Disabled	N/A	Pins 2 & 3 closed	N/A	Pins 2 & 3 closed

SERIAL PORT INTERRUPT SELECTION			
Port 1 (J1)	Port 2 (J2)	P8	P9
IRQ4	IRQ3	Pins 1 & 2 closed	Pins 2 & 3 closed
IRQ3	IRQ4	Pins 2 & 3 closed	Pins 1 & 2 closed

PARALLEL PORT CONFIGURATION					
Port	LPT	IRQ	JP5	JP6	JP10
Enabled	1	7	Pins 1 & 2 closed	Pins 1 & 2 closed	Pins 1 & 2 closed
Disabled	2	5	Pins 2 & 3 closed	Pins 2 & 3 closed	Pins 2 & 3 closed

GAME PORT CONFIGURATION	
Setting	JP7
Enabled	Pins 1 & 2 closed
Disabled	Pins 2 & 3 closed

FACTORY CONFIGURED - DO NOT ALTER	
Jumper	Position
JP11	N/A
JP12	N/A