
DIAMOND FLOWER, INC.

MIO-100

Multi I/O card Card Type Chipset/Controller NEC

Clock, floppy drive interface, game port, parallel port, serial ports (2) N/A I/O Options

Maximum DRAM



CONNECTIONS			
Purpos :	Location	Purpos :	Location
Floppy drive interface	CN1	Game port	J3
External battery connector	J1	Serial port 1	J4
Serial port 2	J2	Parallel port	J5

П		SERIAL PORT C	ONFIGURATION	
	Pc t 1 (J4)	P(t 2 (J2)	S V2/1	S V2/2
	í COM1	í COM2	On	On
	COM2	COM3	Off	On
	COM3	COM4	On	Off

SERIAL PORT INTERRUPT SELECT					
Port 1 (J4) Port 2 (J2) SW1/1 SW1/2 SW1/3 SW1/4					
í IRQ4 Í IRQ3 On Off Off On					
IRQ3	IRQ4	Off	On	On	Off

SERIAL PORT NORMAL/FORCED TRUE CONFIGURATION			
Port 1 (J4)			
í Normal	í Normal	Pins 1 & 2, 4 & 5, 7 & 8 closed	Pins 1 & 2, 4 & 5, 7 & 8 closed
Forced True	Forced True	Pins 2 & 3, 5 & 6, 8 & 9 closed	Pins 2 & 3, 5 & 6, 8 & 9 closed

Continued on next page . . .

DIAMOND FLOWER, INC.

MIO-100

. . . continued from previous page

SERIAL PORT ENABLE/DISABLE SELECT			
P(t 1 (J4)	P(t 2 (J2)	S V2/4	S V2/5
í Enabled	í Enabled	On	On
Enabled	Disabled	On	Off
Disabled	Enabled	Off	On
Disabled	Disabled	Off	Off

SERIAL PORT'S DTE/DCE CONFIGURATION			
Primary serial port J4	Secondary serial port J2		
Jumper JP4	Jumper JP3		
1 TX 1 TX RD RD RTS CTS 9 DTR	1 TX 1 TX RD RD RTS CTS 9 DTR		
DTE DCE	DTE DCE		

PARALLEL PORT CONFIGURATION				
LPT	ort	S V2/3	S V2/6	
í 1	Enabled	Off	On	
2	Enabled	On	On	
N/A	Disabled	N/A	Off	

PARALLEL PORT INTERRUPT SELECT		
IRC SW1/6 SW1/6		
í 7 On Off		
5	Off	On

CLOCK PORT CONFIGURATION		
IRC SW1/i SW1/i		
í IRQ2 Off On		
IRQ5	On	Off

CLOCK PORT INTERRUPT SELECT		
Port SW2/8		
í Enabled On		
Disabled	Off	

GAME PORT CONFIGURATION		
Port SW2/7		
í Enabled	On	
Disabled	Off	