## PROLINK COMPUTER, INC.

## MVGA-T8900CL


Category Video Type Video XVGA

Trident Microsystems, Inc. 1280 x 1024 Video Processor

**Highest Resolution** 

Supported

Data Bus Type Memory Type 16-bit ISA DRAM Maximum Onboard Memory 1MB



CONNECTIONS			
Purpos	Location	Purpos	Location
15-pin analog video port	CN1	VESA Feature conn∈:tor	CN2

ZERO WAIT STATE			
First stage	Second stage	JP1	JP2
í Enabled	í Enabled	Open	Open
Disabled	Disabled	Closed	Closed

ISA BUS SLOT SELECTION			
Size	JP6	JP9/A-C	JP10
8-bit	Open	Open	Closed
16-bit	Open	Closed	Open

SCAN RATE SELECTION		
Setting JP7		
í Default rate	Closed	
48.7KHz	Open	

Continued on next page . . .

## **PROLINK COMPUTER, INC.** MVGA-T8900CL

. . . continued from previous page

BIOS TYPE AUTODETECT		
Setting	Setting JP8	
í Enabled	Open	
Disabled	Closed	

VIDEO MEMORY CONFIGURATION			
Size	1 0	I 1	I 2
256KB	(2) 256K x 4	NONE	NONE
512KB	(2) 256K x 4	(2) 256K x 4	NONE
1MB	(2) 256K x 4	(2) 256K x 4	(4) 256K x 4