## QUATECH, INC.


**WSB-10** 

Card Type Chipset/Controller I/O Options

Waveform Synthesizer Unidentified

Analog/Clock/Digital/Strobe I/O ports N/A

Maximum DRAM



CONNECTIONS						
Pι pose	Lc ation	Pı pose	Lc :ation			
Analog output	BNC1	Clock/Trigger input	BNC3			
Strobe/Clock output	BNC2	Digital output port	H1			

ADDRESS SELECT								
Address	SW1/1	SW1/2	SW1/3	SW1/4	SW1/5	SW1/6	SW1/7	SW1/8
2E0h	On	Off	Off	Off	On	N/A	N/A	On
330h	Off	On	On	Off	Off	N/A	N/A	On
350h	Off	On	Off	On	Off	N/A	N/A	Off

INTERRUPT SELECT					
IRQ	J1				
í Disabled	Pins 1 & 2 closed				
IRQ2	Pins 6 & 12 closed				
IRQ3	Pins 5 & 11 closed				
IRQ4	Pins 4 & 10 closed				
IRQ5	Pins 3 & 9 closed				
IRQ6	Pins 2 & 8 closed				
IRQ7	Pins 1 & 7 closed				

Continued on next page . . .

## QUATECH, INC.

WSB-10

. . . continued from previous page

	I/O CONFIGURATION	
Por	Functic	J1
í BNC2	Strobe output	Pins 2 & 3 closed
BNC2	Clock output	Pins 3 & 4 closed
í BNC3	External clock input	Pins 7 & 8 closed
BNC3	External trigger input	Pins 6 & 7 closed