


JPN CORPORATION CA8262

Card Type
Chipset/Controller
I/O Options
Maximum DRAM

Multi-I/O
Unidentified
Game port, parallel port, serial ports (2)
N/A



CONNECTIONS			
Purpose	Location	Purpose	Location
Game port	P1	Serial port 1	JP1
Parallel port	P2	Serial port 2	JP2

SERIAL PORT 1 CONFIGURATION		
COM/Address	JP3/Jumper A	JP3/Jumper B
COM1/3F8h	Pins 1 & 2 closed	Pins 1 & 2 closed
COM3/3E8h	Pins 2 & 3 closed	Pins 1 & 2 closed
Disabled	N/A	Pins 2 & 3 closed

SERIAL PORT 1 INTERRUPT SELECT - JP4				
IRQ	Jumper A	Jumper B	Jumper C	Jumper D
IRQ4	Pins 2 & 3 open	Pins 1 & 2 closed	Pins 2 & 3 open	Pins 2 & 3 open
IRQ2	Pins 2 & 3 open	Pins 2 & 3 open	Pins 2 & 3 open	Pins 1 & 2 closed
IRQ3	Pins 1 & 2 closed	Pins 2 & 3 open	Pins 2 & 3 open	Pins 2 & 3 open
IRQ5	Pins 2 & 3 open	Pins 2 & 3 open	Pins 1 & 2 closed	Pins 2 & 3 open

SERIAL PORT 2 CONFIGURATION		
COM/Address	JP3/Jumper C	JP3/Jumper D
COM2/2F8h	Pins 1 & 2 closed	Pins 1 & 2 closed
COM4/2E8h	Pins 2 & 3 closed	Pins 1 & 2 closed
Disabled	N/A	Pins 2 & 3 closed

Continued on next page...

SERIAL PORT 2 INTERRUPT SELECT - JP4				
IRQ	umper A	umper B	umper C	umper D
IRQ3	Pins 2 & 3 closed	Pins 1 & 2 open	Pins 1 & 2 open	Pins 1 & 2 open
IRQ2	Pins 1 & 2 open	Pins 1 & 2 open	Pins 1 & 2 open	Pins 2 & 3 closed
IRQ4	Pins 1 & 2 open	Pins 2 & 3 closed	Pins 1 & 2 open	Pins 1 & 2 open
IRQ5	Pins 1 & 2 open	Pins 1 & 2 open	Pins 2 & 3 closed	Pins 1 & 2 open

PARALLEL PORT CONFIGURATION		
LPT/Address	JP3/Jumper E	JP3/Jumper F
LPT1/378h	Pins 1 & 2 closed	Pins 1 & 2 closed
LPT2/278h	Pins 2 & 3 closed	Pins 1 & 2 closed
Disabled	N/A	Pins 2 & 3 closed

PARALLEL PORT INTERRUPT SELECT	
IRQ	JP5
IRQ7	Pins 2 & 3 closed
IRQ5	Pins 1 & 2 closed

GAME PORT	
Setting	JP3/Jumper G
Enabled	Pins 1 & 2 closed
Disabled	Pins 2 & 3 closed