## **IBM CORPORATION** EASY OPTIONS 14.4KBPS INTERNAL MODEM MOD535

**Card Type** Fax, Modem (asynchronous/synchronous)

**Chip Set** Unidentified 14.4Kbps **Maximum Data Rate Maximum Fax Rate** 14.4Kbps 8-bit ISA **Data Bus Fax Class** Class I **Data Modulation Protocol** 

Bell 103/212A


ITU-T V.21, V.22, V.22bis, V.32, V.32bis **Fax Modulation Protocol** 

ITU-T V.17, V.21CH2, V.27ter, V.29

MNP5, V.42bis

**Correction/Compression** 

**Error** 



CONNECTIONS						
Function	Label	Function	Label			
Line out	CN1	Line in	CN2			

SERIAL PORT ADDRESS						
Setting	JP1/A	JP1/B	JP1/C	JP1/D		
í COM1 (3F8h)	Closed	Open	Open	Open		
COM2 (2F8h)	Open	Closed	Open	Open		
COM3 (3E8h)	Open	Open	Closed	Open		
COM4 (2E8h)	Open	Open	Open	Closed		

		INTERRUPT		
Setting	JP1/E	JP1/F	JP1/G	JP1/H
3	Closed	Open	Open	Open
í 4	Open	Closed	Open	Open
5	Open	Open	Closed	Open
7	Open	Open	Open	Closed

## **Proprietary AT Command Set**

See document V1910 for a full command summary.