


# STB SYSTEMS, INC. POWERGRAPH VGA (VER. 2)

<b>Card Type</b>	Video
<b>Video Chip Set</b>	Unidentified
<b>Highest Resolution Supported</b>	1024 x 768
<b>Maximum Onboard Memory</b>	1MB DRAM
<b>Data Bus</b>	16-bit ISA
<b>Video Types Supported</b>	XVGA



CONNECTIONS			
Function	Label	Function	Label
15-pin analog video port	J5	DAC chip socket	U2
DAC chip	U1		
Note: Either U1 or U2 should be installed, but not both.			

USER CONFIGURABLE SETTINGS		
Setting	Label	Position
í Two wait state operation	J1	Pins 2 & 3 closed
Zero wait state operation	J1	Pins 1 & 2 closed
í Card does not use IRQ2/9	J2	Pins 2 & 3 closed
Card uses IRQ2/9	J2	Pins 1 & 2 closed
í Factory configured - do not alter	J3	Pins 1 & 2 closed
í BIOS uses 8-bit I/O	J5	Pins 1 & 2 closed
BIOS uses 16-bit I/O	J5	Pins 2 & 3 closed

DRAM
Note: This card may take 256KB, 512KB, or 1MB of on-board DRAM. The locations of the banks and the configurations of the chips in these banks is unidentified.

Continued on next page. . .

STB SYSTEMS, INC.  
POWERGRAPH VGA (VER. 2)

. . . continued from previous page

VERTICAL SCAN RATE		
Resolution	Scan Rate	J4
640 x 480	60Hz	Pins 1 & 2 closed
800 x 600	56Hz	Pins 1 & 2 closed
1024 x 768	43Hz (interlaced)	Pins 1 & 2 closed
640 x 480	72Hz	Pins 2 & 3 closed
800 x 600	72Hz	Pins 2 & 3 closed
1024 x 768	60Hz	Pins 2 & 3 closed