


NEWCOM, INC.

MODEL 1853, MODEL 1855, MODEL 1859

Card Type	Sound card
Chipset	ESS Technologies, Inc. 1868
I/O Options	CD-ROM interface, game/MIDI port, audio line in, modem speakerphone audio connector, microphone in, speaker out, CD-ROM audio in (3), wavetable header
Data Bus	16-bit ISA
Card Size	Full height, half length



CONNECTIONS			
Function	Label	Function	Label
Audio line in	CN1	ATAPI CD-ROM interface	J6
Microphone in	CN2	Modem speakerphone audio in/out	J11
Speaker out	CN3	Panasonic CD-ROM audio in	J12
Game/MIDI port	CN4	Sony/ATAPI CD-ROM audio in	J13
Mitsumi CD-ROM audio in	J4	Front panel control	JP16
Wavetable header	J5		

USER CONFIGURABLE SETTINGS			
Setting		Label	Position
i	CD-ROM interface supports interrupts 5, 7, 9, 10, 11, and 12	JP5	Pins 1 & 2 closed
	CD-ROM interface supports interrupts 5, 7, 9, 10, 11, and 15	JP5	Pins 2 & 3 closed
Note: Interrupt selection is performed by software. The flash RAM for the ESS chip must be updated if the setting of JP5 is changed.			