


REVEAL COMPUTER PRODUCTS

SC400 PRO 16 (REV. 3)

Card Type	Sound card
Chip Set	Unidentified
Maximum Onboard Memory	None
I/O Options	Line in, microphone in, line out, speaker out, game/MIDI port, audio in - CD-ROM, CD-ROM interfaces (3), PC speaker - internal, wavetable connector
Data Bus	16-bit ISA



CONNECTIONS			
Function	Label	Function	Label
Line in	CN1	CD-ROM interface (Panasonic)	CN7
Microphone in	CN2	CD-ROM interface (Mitsumi)	CN8
Line out	CN3	CD-ROM interface (Sony)	CN9
Speaker out	CN4	Wavetable connector	CN10
Game/MIDI port	CN5	PC speaker - internal (not used)	J2
Audio in - CD-ROM	CN6		

USER CONFIGURABLE SETTINGS		
Function	Label	Position
Factory configured – do not alter (PC speaker amp)	J1	Open
Factory configured – do not alter (microphone select)	JX	Unidentified
Programmable EEPROM enabled	J3	Pins 1 & 2 closed
Programmable EEPROM disabled	J3	Pins 2 & 3 closed

BASE I/O ADDRESS SELECTION	
Address	J4
220	Pins 1 & 2 closed
240	Pins 2 & 3 closed