## MAGNITRONICS B232 MINI 2S1P

Card Type Chip Set

Maximum Onboard Memory


I/O Options

Hard Drives supported Floppy drives supported

Data Bus Card Size Multi-I/O card Unidentified Unidentified

Serial ports (2 RS-232), Parallel port

None None 8-bit ISA Half-length



CONNECTIONS			
Function	Label	Function	Label
Serial port 1	CN1	25-pin parallel port	CN3
Serial port 2	CN2		

PARALLEL PORT ADDRESS SELECTION		
Setting	JP1/E	
LPT2 (378h)	Pins 2 & 3 closed	
LPT3 (278h)	Pins 1 & 2 closed	
Disabled	Open	

SERIAL PORT 1 ADDRESS SELECTION				
Setting	JP1/A	JP1/B	JP!/C	JP1/D
COM1 (3F8h)	Pins 1 & 2 closed	Open	Open	Open
COM2 (2F8h)	Open	Pins 1 & 2 closed	Open	Open
COM3 (3E8h)	Open	Open	Pins 1 & 2 closed	Open
COM4 (2E8h)	Open	Open	Open	Pins 1 & 2 closed
Disabled	Open	Open	Open	Open

SERIAL PORT 2 ADDRESS SELECTION				
Setting	JP1/A	JP1/B	JP!/C	JP1/D
COM1 (3F8h)	Pins 2 & 3 closed	Open	Open	Open
COM2 (2F8h)	Open	Pins 2 & 3 closed	Open	Open
COM3 (3E8h)	Open	Open	Pins 2 & 3 closed	Open
COM4 (2E8h)	Open	Open	Open	Pins 2 & 3 closed
Disabled	Open	Open	Open	Open

Continued on next page . . .

. . . continued from previous page

SERIAL PORT 1 INTERRUPT SELECTION		
IRQ JP2/A		
IRQ4	Pins 2 & 3 closed	
IRQ3	Pins 1 & 2 closed	

SERIAL PORT 2 INTERRUPT SELECTION		
IRQ JP2/B		
IRQ3	Pins 1 & 2 closed	
IRQ4	Pins 2 & 3 closed	

PARALLEL PORT INTERRUPT SELECTION		
IRQ	JP2/C	
IRQ7	Pins 1 & 2 closed	
IRQ5	Pins 2 & 3 closed	