


KOUWELL ELECTRONIC CORPORATION

KW-530/KW-530D

Card Type	Floppy drive controller
Floppy drives supported	360KB, 720KB, 1.2MB, 1.44MB
Data Bus	8-bit ISA



CONNECTIONS

Function	Location
Diskette controller connector	CN1

FLOPPY DRIVE CONTROL ADDRESS SELECTION

Address	J2
Primary	Pins 1 & 2 closed
Secondary	Pins 2 & 3 closed

HARD DRIVE CONTROLLER STATUS REGISTER ADDRESS SELECTION

Address	J2
1F7H (no hard disk controller installed)	Pins 4 & 5 closed
177H (hard disk controller installed)	Pins 5 & 6 closed

USER CONFIGURABLE SETTINGS

Function	Label	Position
» Factory configured - Do not alter	J1	Unidentified

» Factory configured - Do not alter	J3	Unidentified
» Factory configured - Do not alter	RP1	Unidentified
» Factory configured - Do not alter	RP2	Unidentified
1.2MB or 1.44MB drive installed in 8086/8088 or 80286/80386 system	SW1/1	On
1.2MB or 1.44MB drive installed in 80286/80386 system only	SW1/1	Off
» Factory configured - Do not alter	SW1/2	Unidentified
Drive A is 360KB or 720KB	SW1/3	On
Drive A is 1.2MB or 1.44MB	SW1/3	Off
Drive B is 360KB or 720KB	SW1/4	On
Drive B is 1.2MB or 1.44MB	SW1/4	Off

Note: SW1/2 and SW1/3 only function when SW1/1 is in the On position.